

GOLDTAPE 346

SEMI-AUTOMATIC MANUAL DIMENSIONING TAPE SEALING MACHINE

MACHINE DESCRIPTION

Semiautomatic carton sealer with autoadhesive tape for the top and bottom sealing of American-type boxes, for uniform carton size batches, with manual dimensioning. The adjustments are fast and easy, also allowing its use by non-specialist operators. Particularly recommended for high or low boxes. The machine, when combined with infeed and outfeed conveyors, represents a simple, effective and economical packaging station.

TECHNICAL DESCRIPTION

Main machine structure in bent, bolted and painted sheet steel. The boxes are fed by mean of 4 flat drive belts, 2 bottom and 2 top, driven by a single motor. The regulations for the various formats are carried out using hand-wheels.

TECHNICAL DATA

Weight	173 Kg
Standard tape heads	TU2.2 o TU2.3 for adhesive tape (tape width 50 mm)
Legs	Adjustable legs with fix feet
Dimensions of the boxes to seal	L 150 mm to infinite – W 165 to 660 mm H da 100 a 660 mm
Productivity	1300/1500 boxes per hour
Box transfer speed	24 metres / min.
Electrical power supply	Three-phase / Single-phase
Service temperature	+ 5° C to + 35° C
Electrical protection level	IP 54
Installed power	0,25 kW
Plan dimensions	990 X 1157 mm
Bed height (working height)	650 mm

**Specifications subject to change without notice*

OPTIONAL ACCESSORIES

- Single-phase version
- Legs with wheels Ø 80 mm
- Infeed/Outfeed pack table (400x500 mm)
- Roller conveyor in many sizes and extensible roller conveyors (up to 5900 mm)
- Opposite version
- Line kit (consists of: infeed conveyor 790x500 mm equipped with box stop blade and an outfeed conveyor 790x500 mm equipped with box stop bar)
- Tape break/end alarm
- Drive belt timed stop