



GOLDTAPE 80

**SEMI-AUTOMATIC MANUALLY ADJUSTABLE
CARTON SEALER FOR SAME SIZED AMERICAN TYPE BOXES**

MACHINE DESCRIPTION

Semiautomatic carton sealer with autoadhesive tape for the top and bottom sealing of American-type medium and large boxes, for uniform carton size batches, manual dimensioning. The adjustments are fast and easy, also allowing its use by non-specialist operators. The machine, if combined with infeed and outfeed conveyors, represents a simple, fast and economical packaging station.

TECHNICAL DESCRIPTION

Main machine structure in bent, bolted and painted sheet steel. The boxes are fed by means of 2 lower side drive belts driven by a single motor. The regulations for the various formats are carried out by means of hand-wheels.

TECHNICAL DATA

Weight	170Kg
Standard tape heads	TU2.2 or TU2.3 for adhesive tape (tape width 50 mm)
Legs	Adjustable legs with fix feet
Box sizes	L 150 mm to infinite – W 100 to 810 mm – H 120 to 810 mm
Productivity	About 1300-1500 boxes for hour
Box transfer speed	24 metres per minute
Electrical power supply	Three-phase /single-phase
Service temperature	From + 5° C to + 35° C
Electrical protection level	IP 54
Installed power	0,22 kW
Bed height (working height)	650 mm

**Specifications subject to change without notice*

OPTIONAL ACCESSORIES

- Roller conveyors in many sizes
- Single-phase electric
- Leg with casters (diameter 80 mm)
- Adjustable legs with casters (casters diameter: 100 mm - legs extension adjustable 0 to 300 mm – with ruler)
- Reduced height belts (belts height reduced at 65 or 40 mm, suitable for short boxes - to be used with TU2.1)
- Tape break/end alarm
- Drive belt timed stop
- Opposite version